



- **Minimal Architectural Solution:** Provides a clean, modern appearance with a 50% reduced center mullion for enhanced transparency.
- **High-Security Locking:** Equipped with a specially designed high-strength multi-point locking system for improved safety.
- **Thermal Efficiency:** Features a polyamide-profiled hollow center detail to support thermal insulation.
- **Ease of Use:** Designed for simplified production and installation, reducing labor time and complexity.

TECHNICAL SPECIFICATIONS	
SASH WIDTH	1 4/16"
SASH LENGTH	2 15/16"
FRAME LENGTH	1 12/16"
GLASS THICKNESS	1 3/16" - 1 4/16"
MAX. SASH CARRYING CAPACITY	260 lbs
INSULATION BRIDGE	1 3/16"
THE MIDDLE SASH WIDTH	1 5/16" - 3 1/16"

APPLICATION FEATURES	
WATER, AIR INSULATION	✓
ENERGY SAVINGS	✓
SPECIAL STEEL RAIL	✓
FLY SCREEN	✓
MULTI LOCK APPLICATION	✓
EASE OF USE AND FUNCTIONALITY	✓
MINIMAL MIDDLE SASH	✓
45° AND 90° SASH JOINT	✓
3 TRACK FRAME	✓
MONO RAIL FRAME	✓

Clean Lines, Strong Performance
Opens Up Spaces with Confidence.



34 mm middle sash profile at 90°
sash joints allows more light to enter your home.

Special fly screen rail frame and
useful fly screen sash in 90° and 45° sash combinations